



Delo® Protection for Agricultural Equipment



Engine Crankcase

- Delo 400 XSP SAE 5W-40
- Delo 400 XLE SAE 15W-40
- Delo 400 SDE SAE 15W-40
- Delo 400 LE SAE 15W-40
- Delo 400 SD SAE 15W-30**

Coolant System

- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant



Bearings

- Delo Grease ESI® EP 2
- Delo Grease ESI HD EP
- Delo Grease EP



Hydraulic System

- Chevron 1000 THF
- (For units with common THF reservoirs)
- Chevron Synthetic All Weather THF
- (For units with common THF reservoirs)



Differentials & Gear Drives

- Chevron 1000 THF
- (For units with common THF reservoirs)
- Chevron Synthetic All Weather THF
- (For units with common THF reservoirs)



Transmissions (Manual & Automatic)

- Chevron 1000 THF (For units with common THF reservoirs)
- Chevron Synthetic All Weather THF (For units with common THF reservoirs)

Available as ISOCLEAN® Certified

**Severe duty applications typically have lower drain intervals relative to other duty cycles. See OEM recommendations for drain interval recommendations.

The product recommendations provide general guidelines for use in tractors. All tractor manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. You may contact our LUBETEK organization (800-LUBE-TEK) for confirmation of specific OEM specifications.



Delo®

Let's go further™

A Chevron company product

©2017 Chevron U.S.A. Inc. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.

DLPTAGEQST_06-17