

# Chevron Delo® Bumper-to-Bumper Protection for Surface Mining Equipment

## Hydraulic System

- Delo® TorqForce MP (CAT TO-4M)
- Delo TorqForce™ 10W (CAT TO-4)
- Clarity® Synthetic Hydraulic AW
- Rando® HDZ
- Ursa Hydraulic Oil 10W

## Engine Crankcase

- Delo 600 ADF 15-40
- Delo 400 XSP 5W-40
- Delo 400 XLE 15W-40
- Delo 400 SDE 15W-40

## Coolant System

- Delo ELC Advanced Antifreeze/Coolant
- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant

## Differentials & Gear Drives

- Delo TorqForce 50 (CAT TO-4)
- Delo TorqForce FD 60 (CAT FD-1)

## Bearings and Grease Points

- Starplex® HD
- Starplex HD M5
- Starplex Syn EP M5
- Starplex HD M3

## Transmissions

- Delo TorqForce Syn 5W-20 (CAT TO-4)
- Delo TorqForce MP (CAT TO-4M)
- Delo TorqForce 30 (CAT TO-4)

Available as ISOCLEAN® Certified

These product recommendations provide general guidelines. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit [chevron-gsc.force.com/lubeteksupport](http://chevron-gsc.force.com/lubeteksupport) for confirmation of specific OEM specifications.



A Chevron company product

©2023 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.