

Chevron Delo® Bumper-to-Bumper Protection for Wheel Loaders

Hydraulic System


- Delo TorqForce™ 10W (CAT TO-4)
- Delo TorqForce MP
- Clarity® Synthetic Hydraulic AW
- Rando® HDZ

Transmission

- Delo TorqForce MP (CAT TO-4M)
- Delo TorqForce 10W & 30W (CAT TO-4)
- Delo TorqForce Syn 5W-30 (CAT TO-4)

Engine Crankcase

- Delo 600 ADF 10W-30
- Delo 600 ADF 15W-40
- Delo 400 XSP 5W-40
- Delo 400 XLE 10W-30
- Delo 400 XLE 15W-40
- Delo 400 SDE 15W-40



Bearings and Grease Points

- Starplex® HD
- Starplex HD M5
- Starplex Syn EP M5

Gear Drive

- Delo TorqForce 50 (CAT TO-4)
- Delo TorqForce FD 60 (CAT FD-1)

Coolant System

- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant

Available as ISOCLEAN® Certified

These product recommendations provide general guidelines. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit chevron-gsc.force.com/lubeteksupport for confirmation of specific OEM specifications.



A Chevron company product

©2023 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.