

# DELO® 400 XLE SB SAE 15W-40



## Product Information Sheet



Delo 400 XLE SB SAE 15W-40 with ISOSYN® Advanced Technology delivers all the benefits you have come to expect from a Chevron Delo heavy duty engine oil.

Delo 400 XLE SB SAE 15W-40 is a premium synthetic blend, heavy-duty engine oil recommended for naturally aspirated and turbocharged four-stroke diesel engines and four-stroke gasoline engines in which the API CK-4, or API SN service category and SAE 15W-40 viscosity grades are recommended.

### BENEFITS

Delo 400 XLE SB SAE 15W-40 with ISOSYN Advanced Technology provides the same level of protection you expect from an SAE 15W-40 but in a synthetic blend heavy duty engine oil. It is specifically formulated for on-highway applications, including 2017 greenhouse gas (GHG 17) compliant diesel engines with lower CO<sub>2</sub> emissions, in addition to 2010 compliant low emission and off-highway Tier IV diesel engines with Selective Catalytic Reduction (SCR), Diesel Particulate Filter (DPF) and Exhaust Gas Recirculation (EGR) systems calling for SAE 15W-40 premium heavy duty motor oil.

Additionally, Delo 400 XLE SB SAE 15W-40 has excellent performance in Allison heavy-duty transmission units requiring Allison TES-439 approval and provides excellent shear stability and component protection.

It is fully compatible with previous engine models and previous API Oil Service Categories.

Delo 400 XLE SB SAE 15W-40 delivers value through:

- Extended Drain Performance\*
- Exceptional Deposit Control
- Better Low Temperature Pumpability\*\*
- Long Drain Performance
- Minimized Operating Costs
- Excellent Emission Control System Life
- Managed Inventory Costs

\*Results will vary based on the Delo 400 product, operating conditions, and engine types. Always follow OEM recommendations and utilize used oil analysis testing when extending oil drain intervals

\*\*Improved flow rate and pumpability compared to conventional SAE 15W-40



### APPLICATIONS

Delo 400 XLE SB SAE 15W-40 has a wide range of specifications and approvals, it is recommended for today's most modern on-highway low emission designs as well as older on-highway diesel engines. This versatile oil meets stringent emissions standards, making it an ideal choice for various industries, including oil and gas, construction, agriculture, marine, and mining.

Delo 400 XLE SB SAE 15W-40 is approved for:

**API Service Categories** CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4, SN  
**Cummins** CES 20086

**Detroit Fluids Specification (DFS)** 93K222

**Mack** EOS-4.5

**Renault** RLD-3

**Volvo** VDS-4.5

Delo 400 XLE SB SAE 15W-40 is recommended for use:

**ACEA** E11

**Allison** TES-439

**Caterpillar** ECF-3

**DEUTZ** DQC III-18 LA

**DTFR** 15C100 (previously known as MB 228.31)

**Ford** WSS-M2C171-F1

**JASO** DH-2

**MAN** M3775

**MTU** Category 2.1

**For more information contact  
your Chevron Lubricants  
Representative.**

[ChevronDelo.com](http://ChevronDelo.com)

A **Chevron** company product

©2023 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.

**Delo®**  
Let's go further.®