



Havoline®

CHOOSE YOUR ENGINE PROTECTION



CONVENTIONAL



SYNTHETIC BLEND



FULL SYNTHETIC



PROTECTION UP TO
5,000
MILES*

PROTECTION UP TO
5,000
MILES*

PROTECTION UP TO
10,000
MILES**

PROTECTION UP TO
10,000
MILES**

	MOTOR OIL	SYNBLEND	†HAVOLINE SYNBLEND DX SYNTHETIC BLEND	HIGH MILEAGE SYNBLEND	†HAVOLINE PRO-DS FULL SYNTHETIC	†HAVOLINE LIFELONG HIGH MILEAGE FULL SYNTHETIC
HYBRID COMPATIBILITY					0W-16, 0W-20	0W-16, 0W-20
ENGINE POWER					Maximum engine power	Maximum engine power
HIGH-MILEAGE ADVANTAGE				Special conditioners for seals and gaskets		Special conditioners for seals and gaskets
THERMAL STABILITY			Heat resistance	Heat resistance	Enhanced stability +76% thermal breakdown resistance	Enhanced stability +76% thermal breakdown resistance
FUEL ECONOMY			Optimal efficiency retention	Optimal efficiency retention	Exceptional fuel efficiency	Exceptional fuel efficiency
WEAR PROTECTION	Basic lubrication	Anti-wear protection	Anti-wear protection	-25% wear vs. industry standard	-50% wear vs. industry standard	-50% wear vs. industry standard
CLEANLINESS	Less sludge and deposit buildup	Less sludge and deposit buildup	Less sludge and deposit buildup	Less sludge and deposit buildup	Superior protection against buildup and varnish	Superior protection against buildup and varnish

**Guaranteed protection for 10,000 miles, or one year, whichever comes first. Go to havoline.com for details.

*Guaranteed protection for 5,000 miles, or one year, whichever comes first. Go to havoline.com for details.

†GM dexos1™ Gen 3 licensed (0W20, 5W30 viscosity grades).

© 2020-2025 Chevron U.S.A. Inc. All rights reserved. Chevron, the Chevron Hallmark, Havoline, LIFELONG and Deposit Shield are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.