

# Chevron Havoline® Full Synthetic Multi-Vehicle ATF

## DESCRIPTION

Havoline® Full Synthetic Multi-Vehicle Automatic Transmission Fluid (ATF) is a premium, full synthetic transmission fluid with a low viscosity formulation, superior friction control, and dependable protection for use in 6+ speed automatic transmissions of both domestic and import vehicles (model years 2006 and newer, refer to owner's manual). It is approved by Ford and General Motors for use in transmissions and transaxles requiring their latest ATF specifications – DEXRON®-VI<sup>1</sup> and MERCON®-LV.<sup>2</sup> It also exceeds the requirements of JASO 1A-LV, the performance standards created by Japanese automobile manufacturers and recognized by Japanese and Korean carmakers for certifying the ATF for use in their vehicles.

## PRODUCT PERFORMANCE\*

Havoline Full Synthetic Multi-Vehicle ATF delivers value through:

- Maximized transmission life
- Lower maintenance costs
- Improved fuel economy
- Peace of mind

Havoline Full Synthetic Multi-Vehicle ATF is formulated with high purity synthetic base oils and long-lasting viscosity modifiers to meet the demanding requirements of modern vehicles.

- Friction control and performance
- Oxidation stability and wear protection
- Shear stability with exceptional lubrication

*\*Refer to the Chevron Havoline Product Data Sheets on Havoline.com for all performance claim details.*

## PACKAGES

Package Type	Product Number
1 Quart	226536481
6-gal PitPack®	226536687
55-gal Drum	226536982
Bulk	226536990

*Package styles may differ by product, viscosity, plant and region. Please check with your Chevron sales representative.*

<sup>1</sup>DEXRON is a registered trademark of General Motors Corporation.

<sup>2</sup>MERCON is a registered trademark of Ford Motor Company

## ROLE IN THE PRODUCT LINE

- Premium, full synthetic formulation
- For vehicles still under warranty
- Dual-licensed for use in any vehicles requiring Ford MERCON®-LV or GM DEXRON®-VI approvals
- Recommended for most high and low viscosity applications including Honda DW- 1, Hyundai SP-IV, Nissan Matic S and Toyota WS
- Broad coverage - carry fewer OEM-specific ATFs



# Chevron Havoline® Full Synthetic Multi-Vehicle ATF

## APPLICATIONS

### Licensed/approved for use in:

- All Ford vehicles requiring MERCON® LV fluid (MERCON LV license number MLV190802)
- All General Motors and other vehicles specifying DEXRON®-VI, DEXRON®-III, DEXRON®-II or DEXRON® fluid (DEXRON-VI license number J-62318)

### Recommended by Chevron for use in:

- JASO 1A-LV (M315) specification for shifting performance, shear stability and exceptional anti-shudder durability desired by Asian automakers for their high and low viscosity applications
- Voith H55.6335.xx (G607)
- Vehicles built with ZF and Aisin Warner transmissions, where LifeguardFluid 5, LifeguardFluid 8, LifeguardFluid 9, AW-1 or AW-2 fluids are specified
- Hybrid Vehicles where Toyota Type WS fluid or any fluid listed in the table at right is specified
- Most modern transmissions manufactured by European, Asian and North American OEMs, where the standards at right are specified.

All Havoline products, including Havoline Full Synthetic Multi-Vehicle ATF, are backed by Chevron's Limited Product Warranty. Always check your owner's manual to determine the proper automatic transmission fluid for your vehicle. Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

For additional information on this product, please consult the Havoline ATF guide, Havoline Recommendation Guide or a Chevron sales representative.

OEM	Fluid Spec
<b>BMW</b>	ETL-8072B P/N 83 22 0 397 114 P/N 83 22 2 152 426
<b>Chrysler/FCA</b>	Mopar ASRC P/N 68043742AA3 P/N 68218925AA
<b>General Motors</b>	Saturn P/N 22717466
<b>Honda</b>	ATF Type 3.0 ATF DW-1, ATF-Z1
<b>Hyundai/Kia</b>	SP-IV, SP-IV-RR, SP4-M1, WS (NWS-9638), SPH-IV
<b>Jaguar - Land Rover</b>	JLM 20238 JLM 20292 WSS-M2C922-A1
<b>Mercedes Benz</b>	MB 236.41 MB 236.8
<b>Nissan/Infiniti</b>	Matic W
<b>Porsche</b>	P/N 000 043 204 63 P/N 000 043 304 00
<b>Suzuki</b>	Matic-D
<b>Toyota/Lexus</b>	Type T-II, Type T-III, Type-IV, ATF WS (JWS 3324 / NWS 9638)
<b>Volkswagen</b>	G 060 540 A2 G 055 540 A2
<b>Volvo</b>	P/N 1161521 P/N 31 256 774

*Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.*

### To order:

- Check with your Chevron sales representative
- Call Chevron at (800) 822-5823, or
- Email [lubricants1@chevron.com](mailto:lubricants1@chevron.com)

To learn more go to: [Havoline.com](http://Havoline.com)

